

Technical Data: Duct Wrap Film

**Product Description** – A high tack masking film for use in duct and vent wrap applications. The product consists of a blended polyethylene film backing, coated with an acrylic adhesive. Duct Wrapper film is highly tear and puncture resistant which ensures the integrity of the seal around the openings of sheet metal duct work and components. Specially formulated adhesive sticks well to sheet metal surfaces but removes without residue. UV light stabilizer in the product maintains the integrity of the film in case of outdoor exposure.

## **Product Characteristics**

## Construction

Backing Material High strength polyolefin

Adhesive Type Acrylic
Total Thickness 2.5 Mils
Color Blue Tint

## Performance

Tensile Strength (psi)		Test Method
MD	3800	ASTM D 882
TD	3000	ASTM D 882
Elongation (%)		
MD	470	ASTM D 882
TD	950	ASTM D 882

TD 950 ASTM D 88 Adhesion Level High

## Stock Sizes\*

24"x200' (1) roll/box 36"x200' (1) roll/box 48"x200' (1) roll/box

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Hercules Industries assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Hercules product proven defective. For full disclosure of the Limited Warranty, please contact your Hercules representative.



Phone: (800) 356-5350

Fax: (303) 937-0903

<sup>\*</sup>Other sizes available upon request.