



Employee owned. Family founded. Made in the USA.

8" Rigid Aluminum Flex #ALFLX and #MYL

- MODEL #ALFLX - Non-insulated 8' lengths
- MODEL #MYL - Insulated 8' lengths

FEATURES:

- Lightweight
- Easy to cut and install
- Very flexible-can be bent, straightened and rebent to accommodate any installation
- Can be ovalized easily by hand to accept any type outlet or collar
- May be used in both positive and negative pressure applications
- Very good air handling properties with minimal air leakage and low friction loss
- Puncture resistant outer mylar skin serves as a tough, durable vapor barrier on Model #MYL

PHYSICAL DATA:

- U.L. Listed - Air duct material Class 1 per U.L. 181
- Conforms to MFPA 90A and NFPA 90B
- Sizes available 3" - 24"
- Material - Type 3003 Aluminum
- Insulation - 1½" Fiberglass wrap x .75 lb. Density.
1½" Thermal/acoustic Flame - Attenuated Glass
- Vapor Barrier - Metalized and clear polyester film laminated with a reinforcing fiber glass nylon string encapsulated (silver)
- Maximum Velocity: 5,000 F.P.M.
- Maximum Positive & Negative Pressure: 6" - 12" 12" w.c. 14" - 24" 8" w.c.
- Applications: Low to High SMACNA classifications
- Temperature Range: - 100 degrees F to + 435 degrees F

FOR MORE INFORMATION CALL YOUR LOCAL BRANCH

ON EACH PIECE OF #MYL LOOK FOR THIS LABEL